



# EPPCO BENZYNA HD SF

## PRODUCT DESCRIPTION

**EPPCO BENZYNA HD SF** is a monograde engine oil developed for gasoline and naturally aspirated diesel engines. It is ideally suited for use in cars and light trucks where the customers' needs can be met with a cost-effective lubricant using standard oil change periods. **BENZYNA HD** exceeds the API classification SF and CC

## APPLICATIONS

- ◆ Good performance in gasoline and diesel engines
- ◆ Control of sludge and deposits
- ◆ Advanced detergent/dispersant properties
- ◆ Resistance to oil thickening

## PERFORMANCE STANDARDS

**BENZYNA HD SF** meets and exceeds the following International specifications:  
API SF/CC

*Always follow equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.*

## BENEFITS

**BENZYNA HD SF provides:**

- ◆ Good performance in gasoline and diesel engines
- ◆ Control of sludge and deposits
- ◆ Advanced detergent/dispersant properties
- ◆ Resistance to oil thickening

Technical Data*		
SAE Grade	40	50
Kinematic Viscosity		
mm <sup>2</sup> /s @ 40°C	144	211
mm <sup>2</sup> /s @ 100°C	14.25	18.5
Viscosity Index	96	97
Flash Point, COC, °C	248	260
Pour Point, °C	-15	-9
Product Code	310007	310015

\*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

### HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the EPPCO Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.