



EPPCO ADVANCED V40

PRODUCT DESCRIPTION

EPPCO ADVANCED V40 is a robust performance diesel engine oil for use in high output and turbocharged engines. It is available in SAE 15W-40 viscosity grade and has been developed to meet API service classification CF-4 for mixed fleet operations where European, US and Japanese heavy and light duty trucks are used.

APPLICATIONS

- ◆ Modern turbocharged and intercooled heavy goods vehicles
- ◆ Heavy earth moving equipment used in the construction industry
- ◆ Long distance coach operations
- ◆ Mixed fleet vehicle operations
- ◆ High speed diesels used in offshore marine applications
- ◆ Stationary power generation units using high speed diesel engines

PERFORMANCE STANDARDS

ADVANCED V40 meets the following International specifications:

API CF-4

Always follow the equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.

BENEFITS

ADVANCED V40 provides:

- ◆ **Excellent Engine Cleanliness**
- ◆ **Helps Maintain Engine Efficiency**
- ◆ **Proven TBN Retention Reserve**

Technical Data*	
SAE Grade	15W-40
Kinematic Viscosity mm ² /s @ 40°C	123
mm ² /s @ 100°C	16
Viscosity Index	138
Flash Point, COC, °C	230
Pour Point, °C	-30
BN No. ASTM D2896	12
Sulphated Ash % mass	1.69
Product Code	300093

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.