

EPPCO ADVANCED 660X

PRODUCT DESCRIPTION

EPPCO ADVANCED 660X are superior quality diesel engine oils available in SAE 15W-40 & SAE 20W-50 viscosity grades. EPPCO ADVANCED 660X provides proven engine protection of diesel engines operating in both on and off-highway service applications. **ADVANCED 660X** are recommended by EPPCO for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

APPLICATIONS:

- ◆ Mixed fleets of automotive diesel truck manufacturers
- ◆ Especially tailored for working in equipments running on low Sulphur fuel
- ◆ Off-highway vehicles and plant equipment
- ◆ Diesel generator sets
- ◆ All vehicle makes used in long distance transport

PERFORMANCE STANDARDS

EPPCO ADVANCED 660X meets the performance requirements of following OEM and International Specifications:

API CG-4

Always follow equipment manufacturer's recommendations for required lubricant performance levels.

BENEFITS

EPPCO ADVANCED 660X provides:

- ◆ Excellent engine cleanliness
- ◆ Mixed fleet capabilities
- ◆ Trouble free operation between service intervals
- ◆ Reduced maintenance capabilities

Technical Data*		
SAE Grade	15W-40	20W-50
Kinematic Viscosity, ASTM D445, mm ² /s		
mm ² /s @ 40°C	112.0	168.0
mm ² /s @ 100°C	14.8	19.10
Viscosity Index, ASTM D2270	138	129
Flash Point, COC, ASTM D92, °C	226	238
Pour Point, ASTM D97 °C	-30	-27
BN No., ASTM D2896, mg KOH/g	8.55	8.55
Product Code	300008	300021

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.