

EPPCO MANTRANS ULTRA

PRODUCT DESCRIPTION

EPPCO MANTRANS ULTRA fluids are a range of superior quality axle oils suitable for older generation trucks and construction plant equipment. They contain balanced extreme pressure chemical technology meeting the API GL-5 classification designed to minimise scuffing and scoring of gear surfaces under high speed, extremely high torque and shock load operation. In addition, thermally stable oxidation inhibitors assist in optimum oil service life.

APPLICATIONS

- Suitable for heavy duty service in hypoid and spiral bevel differentials
- Double reduction rear axles in heavy vehicles
- Hub reduction gears in off-highway heavy construction equipment
- Some manual gearboxes (constant or non-synchromesh), auxiliary gearboxes and transfer boxes
- Steering boxes

PERFORMANCE STANDARDS

MANTRANS ULTRA meets and exceeds the following International specifications:

API	GL-5
US Military	MIL-L-2105D

Always follow equipment manufacturer's recommendations for the required lubricant performance level and oil drain interval.

BENEFITS

MANTRANS ULTRA provides:

- ◆ High load carrying capacity
- ◆ Superior oxidation resistance
- ◆ Optimum service life

Technical Data*		
SAE Grade	90	140
Kinematic Viscosity mm ² /s @ 40°C	180	358
mm ² /s @ 100°C	17	25
Viscosity Index	95	95
Pour Point, °C	-12	-12
Product Code	322005	322006

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the EPPCO Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.