

EPPCO ADVANCED V60

PRODUCT DESCRIPTION

EPPCO ADVANCED V60 is a robust engine oil developed for the lubrication of heavy goods vehicles used in general transport, earthmoving, quarrying and construction equipment as well as stationary diesel engines requiring API CF quality engine oil. It is designed specifically for use in naturally aspirated and light turbocharged diesel engines. Formulated for moderate to severe service depending on the diesel fuel Sulphur level and oil change frequency.

APPLICATIONS

- Heavy goods vehicles in general transport
- Construction and heavy earthmoving equipment
- Engine oils used in mobile air compressors
- Light trucks with diesel or gasoline engines
- Older model passenger cars
- Certain transmissions for earthmoving equipment

PERFORMANCE STANDARDS

ADVANCED V60 meets the following International specification:

API CF

Always follow equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.

BENEFITS

ADVANCED V60 provides:

- Engine Protection
- **♦** Excellent Engine Cleanliness
- Suitable for harsh operating conditions

Technical Data*	
SAE Grade	50
Kinematic Viscosity	
mm ² /s @ 40°C	264
mm ² /s @100°C	21.5
Viscosity Index	97
Flash Point, COC, °C	268
Pour Point, ⁰ C	-9
BN ASTM D2896	10.7
Product Code	300101

^{*}The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the EPPCO Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. Handled correctly there are no special precautions suggested.

Issued by ENOC marketing LLC, Dubai, U.A.E. Updated on November 2020 - PB PDS V2301120