

EPPCO MANTRANS PREMIUM PLUS SYN

PRODUCT DESCRIPTION

EPPCO MANTRANS PREMIUM PLUS SYN is Synthetic based high quality mild extreme pressure multigrade gear and transmission oils suitable for use in cars, trucks, buses, construction plant equipment. It is blended from high quality synthetic base oils and incorporate balanced, extreme pressure chemical technology to minimise scuffing and scoring of transmission gears operating in high speed and high torque conditions where API GL-4 performance level is required. Especially recommended for trucks and coaches equipped with ZF manual gear boxes

APPLICATIONS

- Manual synchromesh transmissions for cars, trucks, and buses
- ♦ Spiral-Bevel final drive axles in certain makes of vehicles
- Automotive steering boxes
- Tractor and off-road heavy equipment, transaxles, and differentials

PERFORMANCE STANDARDS

MANTRANS PREMIUM PLUS SYN meets and exceeds the following International specifications:

API GL-4

Always follow equipment manufacturer's recommendations for the required lubricant performance level and oil drain interval.

BENEFITS

MANTRANS PREMIUM PLUS SYN provides:

- Robust oxidation and corrosion protection
- Strong wear protection for gears and bearings
- Compatibility with different materials in gearbox
- High levels of shear stability
- Extended oil drain capability reducing overhaul and maintenance downtime
- Exceptional thermal stability and resistance to high temperature oxidation

Technical Data*	
SAE Grade	75W-90
Kinematic Viscosity	
mm ² /s @ 40 °C	94.6
mm ² /s @100 °C	14.6
Viscosity Index	162
Flash point °C	206
Product Code	322016

^{*}The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the EPPCO Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.

Issued by ENOC Marketing LLC, Dubai, U.A.E. Last Updated on January 2021- MS PDS V3050121

^{*}Before changing the product, OEM (Original Equipment Manufacturer) guide should be checked, oil changes shall be carried out in accordance with the OEM recommendation