

# **EPPCO BENZYNA X-TREME 5W-50**

## **PRODUCT DESCRIPTION**

**EPPCO BENZYNA X-TREME 5W-50** is **fully synthetic gasoline engine oil** for the latest model passenger cars requiring performance specification API SN developed to provide maximum protection. It is available in SAE 5W-50 viscosity grade to provide efficient lubrication at extreme low and high temperatures. Advanced formulation keeps oil pressure sustainable in all city/highway driving conditions. Compatible for all cars running on lead free gasoline.

### APPLICATIONS

- High powered gasoline engines recommending SAE 5W-50 viscosity
- For light duty diesel passenger cars

#### PERFORMANCE STANDARDS

**EPPCO BENZYNA X-TREME 5W-50 is** formulated with additive technology that meets the testing requirement of following International specifications:

API SN ACEA A3/B4

Always follow equipment manufacturer's recommendations for required lubricant performance level and oil drain intervals.

## BENEFITS

#### EPPCO BENZYNA X-TREME 5W-50 provides:

- Optimum power protection in high performance vehicles
- Resistance to oil thickening during in service usage
- Excellent protection against wear
- Excellent low temperature easy starting
- Helps in oil consumption control

Technical Data*	
SAE Grade	5W-50
Density g/ml	0.853
Kinematic Viscosity mm <sup>2</sup> /s @ 40°C	113.2
Kinematic Viscosity mm <sup>2</sup> /s @100 <sup>o</sup> C	18.5
Flash Point COC	230
Pour Point, <sup>0</sup> C	-39
TBN, mg of KOH/g	10.0
Product Code	310035

\*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

#### HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the EPPCO Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.

Issued by ENOC Marketing LLC, Dubai, U.A.E. Last updated on January 2021 MS PDS V2240121