

# EPPCO TRACTOR STO

## PRODUCT DESCRIPTION

**EPPCO TRACTOR STO** lubricants are high quality, multi-purpose, multigrade oils designed primarily for use in agricultural equipment and are commonly referred to as STOU (Super Tractor Oil Universal) oils. These products are recommended as a “all year” oil meeting most tractor manufacturers specifications and providing excellent performance in a variety of tractor and agricultural machinery applications, hydraulics, transmissions, and engine etc. They have the added benefit of reducing lubricant inventory by virtue of having one oil for most applications.

## APPLICATIONS

- ◆ Agriculture tractors Ford, Massey Ferguson and others recommending STOU applications
- ◆ Mixed fleet agriculture equipment
- ◆ Tractor universal transmission meeting John Deere J20 A, MF M 1145 specifications
- ◆ Transmissions requiring API GL-4 and Allison C-4 fluid
- ◆ Hydraulic systems with performance meeting ISO HV 68/100

## PERFORMANCE STANDARDS

**TRACTOR STO** meets and exceeds the following OEM and International specifications:

FORD	M2C 159B	Allison	C-4
API	GL-4	API	CG-4/CF-4/CF/CE
MIL	MIL-L-2104D	ZF	TE-ML 06B/06C/07B
John Deere	JDM J27	Massey Ferguson	CMS M1139, M1144, M1145

***Always follow equipment manufacturer's recommendation for required lubricant performance levels and oil drain intervals.***

## BENEFITS

### TRACTOR STO provides:

- ◆ Rationalisation requiring only one oil for all farm equipment lubrication
- ◆ Savings on inventory cost, ordering and administration
- ◆ Protection for equipment against potential damage using incorrect oil
- ◆ Extended equipment life by ensuring the right oil is used every time
- ◆ Robust additive technology that ensures smoother, quieter transmission and wet brake operation
- ◆ Reduced maintenance costs when compared with using individual oils

Technical Data*			
SAE grade	15W-30	15W-40	20W-40
Density @ 15 °C	0.880	0.889	0.898
Viscosity			
mm <sup>2</sup> /s @ 100°C	12	13	13
mm <sup>2</sup> /s @40°C	87	105	116
Viscosity Index	130	125	105
Flash point COC °C	230	200	200
Pour Point, °C	-40	-30	-21
Product Code	362002	362004	362003

\*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

## HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the EPPCO Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.