

EPPCO BENZYNA FLEX ENERGY SN

PRODUCT DESCRIPTION

EPPCO BENZYNA FLEX ENERGY SN 5W-30 is fully synthetic petrol engine oil, formulated with the latest technology that meets the requirements of API SN Plus. It is specifically designed with advanced "Dual Shield" formula that provides two levels of protection:

- Essential protection: Class leading engine sludge, engine wear & oil thickening protection
- Tailored protection: Class leading Performance capabilities include Low Speed Pre-Ignition (LSPI) reduction in GDI turbocharged engines, Turbocharger deposit protection & Engine oil aeration protection.

EPPCO BENZYNA FLEX ENERGY SN 5W-30 is meeting the API SN Plus, ILSAC GF-5 and GM dexos1 Generation 2 specifications. Compatible with all vehicles running on lead free gasoline, ethanol, LPG and CNG

APPLICATIONS

- ◆ SAE 5W-30 is recommended for all modern Americans/Japanese/Korean/European/Chinese petrol vehicles with multi fuel use.
- ◆ Excellent fuel-efficient motor oil meeting API SN Plus, ILSAC GF- 5 category.

PERFORMANCE STANDARDS

BENZYNA FLEX ENERGY SN 5W-30 is formulated with additive technology that has been tested to meet the following International specifications requirements:

API SN Plus, ILSAC GF-5
 GM dexos1 Gen 2 approved- SAE 5W- 30

Always follow equipment manufacturer's recommendations for required lubricant performance level and oil drain intervals.

BENEFITS

BENZYNA FLEX ENERGY SN 5W-30 provides:

- ◆ Low friction formula helps improve fuel mileage.
- ◆ Prevent engine damage by providing outstanding LSPI protection
- ◆ Excellent Piston / Rings cleanliness which increase engine and oil life.
- ◆ Enhance seal protection which result in reduction in oil leakage.
- ◆ Minimize corrosion due to stop-start driving.
- ◆ Excellent protection for high performance engines.
- ◆ Enhance After Treatment Devices (ATD) protection.
- ◆ Control high temperature oxidation, deposits and prevent sludge and other deposits

Technical Data*	
SAE Grade	5W-30
Density kg/m ³	0.846
Kinematic Viscosity mm ² /s @ 40°C	65.5
Kinematic Viscosity mm ² /s @100°C	10.8
Viscosity Index	165
Flash Point COC	220
Pour Point, °C	-42
Product Code	310038

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the EPPCO Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.