

BENZYNA GREEN

PRODUCT DESCRIPTION

BENZYNA GREEN is an advanced low SAPS (Sulphated Ash, Phosphorous & Sulphur) high technology 100% fully synthetic engine oil for light vehicles gasoline, CNG and diesel engines requiring low emission performance specification meeting ACEA C3 and API SN. Developed to provide maximum protection for all passenger cars, MPVs, SUVs fitted with low emission engines and particulate filters, EGR and catalytic converters. Product imparted with friction modifier is available in SAE 5W-30 and SAE 5W-40 viscosity grade to provide maximum fuel saving and to meet long drain requirements. Compatible to all vehicles running on lead free gasoline.

APPLICATIONS

- ◆ All makes of light duty vehicles with natural and Turbo charged – Passenger cars, MPs, SUVs using gasoline, CNG and diesel.
- ◆ Vehicles fitted with state-of-the art exhaust gas treatment system such as particulate filters, EGR and catalytic converters to meet low emission requirements
- ◆ Compatible with other engine oils but not recommended to mix with other brands to enhance the life of exhaust gas treatment parts.
- ◆ Compatible with seals and gaskets.

PERFORMANCE STANDARDS

BENZYNA GREEN is formulated with additive technology that has been tested to meet the performance requirements for following International specifications:

API SN
 ACEA C3

Always follow equipment manufacturer's recommendations for required lubricant performance level and oil drain intervals.

BENEFITS

BENZYNA GREEN provides:

- ◆ Protects and enhance Exhaust gas treatment gadgets such as particulate filters, Catalytic converters due to low ash technology, thus suitable for low emission engines
- ◆ Increase the catalyst life because of low phosphorous level.
- ◆ Superior resistance to oil thickening/sludge formation, outstanding deposit control and improve engine life
- ◆ Outstanding fuel economy and increase oil drain interval and reduce oil top-up
- ◆ Excellent protection against wear
- ◆ Resistance to nitration and oxidation associated with gas fuels and
- ◆ Excellent low temperature easy starting, so termed as all weather oil

SAE Grade	5W-40	5W-30
Density kg/m ³	0.8413	0.8402
Kinematic Viscosity mm ² /s @ 40°C	86.63	66
Kinematic Viscosity mm ² /s @ 100°C	14.34	11.5
Viscosity Index	172	170
Flash Point COC	230	220
Sulphated Ash	0.78	0.78
Pour Point, °C	-39	-39
Product Code	310031	310030

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.