

EPPCO GRAXA MP GREASE

PRODUCT DESCRIPTION

EPPCO GRAXA MP are high quality, lithium greases suitable for a wide range of applications. It is available in NLGI 2 and 3 consistencies. These are formulated for use in automotive equipment and general lubrication for use in temperatures up to 120°C and where water contamination can be present. The high-quality base oils used in the manufacture of these greases have good resistance to oxidation and because of their low pour point, they provide lubrication at temperatures down to -20°C.

APPLICATIONS

- ◆ Automotive water pump bearings, steering joints, and other chassis plain and anti-friction applications
- ◆ Centralised grease systems (No. 2)
- ◆ Mobile equipment

RECOMMENDATIONS

GRAXA MP minimises wear under normal bearing load conditions and resists water wash-out, especially where equipment is constantly working under damp or wet conditions. It is also effective over a wide temperature range and protects against rust and corrosion. Where vehicles are lubricated by centralised grease systems, **GRAXA MP** offers excellent pumpability characteristics.

Always follow equipment manufacturer's recommendation for required grease performance and re-lubrication periods.

BENEFITS

GRAXA MP provides:

- ◆ Resistance to water wash-out
- ◆ Suitability in wide temperature range
- ◆ Good pumpability
- ◆ Good mechanical stability
- ◆ Multifunctional use

Technical Data*		
	2	3
NLGI Grade	2	3
Dropping point, °C	204	204
Penetration, Worked @ 25°C	280	236
Colour	Light Brown	Light Brown
Oil Viscosity		
mm ² /s @ 40°C	200	200
mm ² /s @ 100°C	17.50	17.5
Timken OK load, Kg	22	25
Operating temperature range °C	-25 to 120	-20 to 120
Product Code	324002	324003

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the EPPCO Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.