

EPPCO BENZYNA PREMIUM

PRODUCT DESCRIPTION

EPPCO BENZYNA PREMIUM is a modern gasoline engine oil that meets the testing requirements of latest API SL performance specification. Developed to provide maximum protection for use in modern passenger cars including low emission engines and high-performance vehicles. It is suitable for all types of driving conditions (city, highway and harsh) and is available in a range of SAE viscosity grades, to meet market conditions. Compatible for all cars running on lead free gasoline and catalytic converters.

APPLICATIONS

- All makes of passenger cars
- ♦ High performance normally aspirated and turbocharged gasoline engines
- Four stroke motorcycle engines where motor oils are recommended
- Japanese and American manufactured cars
- Light commercial vehicles

PERFORMANCE STANDARDS

BENZYNA PREMIUM meet the testing requirements of following International Specifications: API SL

Always follow equipment manufacturer's recommendations for required lubricant performance level and oil drain intervals.

BENEFITS

BENZYNA PREMIUM provides:

- ♦ The highest level of engine protection for all manufacturers
- Superior resistance to oil thickening
- Excellent protection against wear
- Low oil consumption and engine deposits
- Easy all year round starting

• Eddy an year rearia starting				
	Technical Data*			
SAE Grade	10W-30	10W-40	15W-40	20W-50
Kinematic Viscosity mm ² /s @ 40°C	71.0	95	110	160
Kinematic Viscosity mm ² /s @100°C	10.9	14	15.0	18.0
Viscosity Index	142	151	138	125
Flash Point, COC, ⁰ C	216	230	230	240
Pour Point, ⁰ C	-33	-30	-27	-24
Product Code	310020	310009	310010	310004

The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the EPPCO Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.