



EPPCO BENZYNA SUPER SG

PRODUCT DESCRIPTION

ENOC BENZYNA SUPER is a robust gasoline engine oil, available in a range of viscosity grades which meets the API SG specification for gasoline engines. Blended from high quality base oils and advanced additive technology will provide excellent service for heritage passenger cars and light commercial vehicles.

APPLICATIONS

- ◆ Passenger cars with multivalve engines
- ◆ Older model cars requiring API SG specification
- ◆ Light commercial trucks with gasoline or light duty diesel engines
- ◆ Motorcycles where four-stroke gasoline engine oils are recommended
- ◆ Portable gasoline engine generator sets

PERFORMANCE STANDARDS

BENZYNA SUPER meets and exceeds the following International specifications

API SG

Always follow equipment manufacturer's recommendations for required lubricant performance level and oil drain intervals.

BENEFITS

BENZYNA SUPER provides:

- ◆ Superior resistance to oil thickening
- ◆ Excellent protection against wear
- ◆ Low engine deposits
- ◆ Easy all year round starting

Technical Data*		
SAE Grade	15W-40	20W-50
Kinematic Viscosity mm ² /s @ 40°C	112	166
mm ² /s @ 100°C	15.28	18.5
Viscosity Index	142	125
Flash Point, COC, °C	230	236
Pour Point, °C	-27	-34
Product Code	310025	310003

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the EPPCO Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.