

# EPPCO GRAXA LX GREASE

## PRODUCT DESCRIPTION

**EPPCO GRAXA LX** are high performance lithium complex greases with extreme pressure properties, developed for automotive wheel bearing lubrication where they can operate at high temperatures. They have excellent load carrying and anti-wear properties in both steel-on-steel and steel-on-bronze applications. That contain an effective oxidation and rust inhibitor and have low wash-out properties that are important performance requirements for wheel bearing lubrication.

## APPLICATIONS

- ◆ Automotive vehicles
- ◆ Excellent high temperature control under severe breaking
- ◆ Suitable for heavily loaded bearings
- ◆ General mobile equipment
- ◆ Effective temperature range -15°C to 150°C

***Always follow equipment manufacturer's recommendation for required grease performance and re-lubrication periods.***

## BENEFITS

### GRAXA LX provides:

- ◆ Excellent extreme pressure properties
- ◆ Resistance to water wash-out
- ◆ Suitability in high temperature applications
- ◆ Good pumpability
- ◆ Good mechanical stability

Technical Data*		
NLGI Grade	2	3
Dropping point, °C	260	260
Penetration, Worked @ 25°C	280	235
Oil Viscosity		
mm <sup>2</sup> /s @ 40°C	170	170
mm <sup>2</sup> /s @ 100°C	16	16
Timken OK load, Kg	25	19
Operating temperature range °C	-15 to 150	-15 to 150
Product Code	324011	324012

\*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

### HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the EPPCO Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.

Issued by ENOC Marketing LLC., Dubai, U.A.E.  
 Last Updated on January 2021- MS  
 PDS V3050121