



EPPCO BENZYNA 2T

PRODUCT DESCRIPTION

EPPCO BENZYNA 2T is an economical quality two-stroke engine oil that has been developed for small to medium size air-cooled two-stroke engines used in motor-cycles, scooters and three wheeler light passenger vehicles. Formulated with a modern low ash additive system which offers protection against scuffing of piston rings and liner wear by minimising piston ring deposits.

APPLICATIONS

- ◆ All makes of two-stroke engines
- ◆ Three wheeler light passenger vehicles powered by two-stroke engine
- ◆ Chainsaws and in portable equipment powered by two-stroke engine

PERFORMANCE STANDARDS

BEZYNA 2T meets and exceeds the following International specification:

API TA

Always follow equipment manufacturer's recommendation for required lubricant performance levels.

BENEFITS

BENZYNA 2T provides:

- ◆ Control of engine deposits to prevent pre-ignition
- ◆ Consistent power output
- ◆ Supports acceptable engine service life

Mix BENZYNA 2T with petrol

BENZYNA 2T mixes readily with petrol as a "premix" and is equally suitable for metered lube injection systems. The best advise on mixing is to:

- ◆ Fill the tank half with petrol
- ◆ Pour in the correct amount of oil
- ◆ Add the remainder of petrol
- ◆ Follow the manufacturers' recommendations for mixing oil to petrol ratios.

Technical Data*	
Kinematic Viscosity	
mm ² /s @ 40°C	58
mm ² /s @ 100°C	8.2
Flash Point, PMCC, °C	112
Sulphated Ash %m	0.04
Pour Point, °C	-18
Product Code	320005

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the EPPCO Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.