

# EPPCO STEPTRON SYN OEM

## PRODUCT DESCRIPTION

**EPPCO STEPTRON SYN OEM** is a 100% synthetic automatic transmission fluid designed specifically for use in passenger cars, commercial vehicles, and Off-Highway automatic transmission with outstanding performance in American, Japanese, Korean and European equipment's. **EPPCO STEPTRON SYN OEM** provides the excellent friction durability and anti-shudder performance required by ASIAN transmission manufacturers.

## APPLICATIONS

**Eppco Steptron Syn OEM** can be used in North American, European, and Asian vehicles. It is compatible with most high performance stepped automatic transmissions and provides premium performance in older vehicles. Steptron Syn OEM is developed for standard viscosity applications and has proven will in low-viscosity applications:

- ◆ Passenger car automatic transmissions and power steering
- ◆ Commercial vehicle automatic transmission and power steering
- ◆ Off-highway and construction equipment automatic transmissions

## PERFORMANCE STANDARDS

**STEPTRON SYN OEM** is suitable for use requiring the below OEM and International specifications:

Specification	Typical Application
Allison C4	Off-Highway
Allison TES-295	Commercial Vehicles: 100000 kms
Ford Mercon V	Passenger Cars
GM Dexron-IIIH	Passenger Car
GM Dexron-VI	Passenger Car (Low viscosity)
MB-Approval 236.1, 236.5, 236.6, 236.6, 236.9	Daimler passenger cars and commercial vehicle applications
MAN 339 Type V-2	Buses with Voith transmissions up to 120000 kms
MAN 339 Type Z-1, Z-2, Z3	Buses with ZF Transmissions, up to 30K, 60K & 120K Kms
Voith H55.6336	Buses (120000 kms)
Volvo 97340	Construction Equipment (Loaders)
Volvo 97341	Construction Equipment (F Series loaders)
ZF TE-ML 02F	Manual/Automated for vans, trucks, and buses
ZF TE-ML 04D	Marine transmission
ZF TE-ML 05L	Axle Hydraulic fluid
ZF TE-ML 09	Power steering
ZF TE-ML 11A, 11B	Passenger car
ZF TE-ML 14A, 14B & 14C	ZF Ecomat Transmissions up to 30K, 60K & 120K Kms
ZF TE-ML 16L, 16M	Rail Vehicle transmission
ZF TE-ML 17C	Forklift truck
ZF TE-ML 20C	ZF Ecolife transmissions up to 120000 kms
Aisin Warner AW-1*	Can be used for these applications outside of warranty
Audi: G 055 025 A2 (TL52025), G 052 162 A1 (TL52162), G 052 990 (TL52990)	Passenger Cars
BMW: ETL-7045E, ETL-	Passenger Cars

Issued by ENOC Marketing LLC, Dubai, U.A.E

Last updated on January 2021- MS

PDS V2060121

8072B, LA2634, LT71141	
JASO 1-A	Japanese/Korean Passenger Car requirements
Chrysler ATF+3/4, Mopar AS68RC	Passenger Cars
Ford FNR5	Passenger Cars
Honda Z-1	Passenger Cars
Hyundai: SP-II, SP-III, SPH-IV*, NWS-9638*	Passenger Cars (*Can be used for these applications outside of warranty)
KIA: SP-II, SP-III, Red-1	Passenger Cars
JATCO 3100 PL085	Passenger Cars
JWS 3309, JWS 3324, 3314, 3317	Passenger Cars
Mazda: ATF-M III, ATF-MV	Passenger Cars
Mitsubishi Diamond SP-II, SP-III, ATF-J2	Passenger Cars
Nissan N402, Matic-D/J/K, Matic-S	Passenger Cars
Subaru ATF, ATF-HP	Passenger Cars
Suzuki 3317, 3314	Passenger Cars
Toyota T-II/T-III/T-IV	Passenger Cars
Toyota WS (JWS 3324)	Can be used for these applications outside of warranty
Volkswagen: G 055 025 A2 (TL52025), G 052 162 A1 (TL52162), G 052 990 (TL52990)	Passenger Cars
Volvo passenger car (4 to 6 speed AT)	Passenger Cars
ZF TE-ML 11B, ZF Lifeguard fluid 6	Can be used for these applications outside of warranty

**Always follow equipment manufacturer's recommendation for required lubricant performance levels and oil drain intervals.**

## BENEFITS

### STEPTRON SYN OEM provides:

- ◆ Suitable for multi vehicle Automatic Transmission
- ◆ Excellent friction durability and anti-shudder performance
- ◆ Extended long drain intervals
- ◆ Very good low temperature fluidity

Technical Data*	
<b>Colour</b>	<b>Red</b>
Viscosity mm <sup>2</sup> /s @ 100°C	7.7
Viscosity mm <sup>2</sup> /s @40°C	37.71
Brookfield @-40°C, cP	15780
Flash Point, °C	210
Viscosity Index	168
Product Code	321009

\*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

### HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.

Issued by ENOC Marketing LLC, Dubai, U.A.E  
 Last updated on January 2021- MS  
 PDS V2060121