

EPPCO THERMA SPECIAL

PRODUCT DESCRIPTION

EPPCO THERMA Special Oil are highly refined paraffinic oil suitable for a range of heat transfer applications in both closed and open systems with pumped circulation.

APPLICATIONS

- ◆ If used for open system, the operating temperature shall not exceed 210°C for safety purposes.
- ◆ Recommended for use in indirect heating and cooling installations in all kinds of Industrial processes operating at bulk oil temperatures up to maximum 320°C for ISO 32.
- ◆ Closed systems with inert gas sealing up to 290°C.
- ◆ Heating of reaction vessels, driers, moulding machines.
- ◆ Fast Quenching applications.

PERFORMANCE STANDARDS

ASTM D-3520 (GM Quench meter) for ISO 22 VG oil

Averages quench time (sec) 13.5

Relative cooling Index 202

DIN 51502 class L

ISO 6743/12 class L QB family

Always follow the equipment manufacturer's recommendations.

BENEFITS

THERMA Oil provides:

- ◆ High resistance to thermal cracking and decomposition.
- ◆ Maximum energy transfer and improved operating efficiency.
- ◆ Low temperature flow characteristics at start-up.
- ◆ Good resistance to the formation of deposits.
- ◆ Good thermal stability.

Technical Data*		
SAE GRADE	32	22
Density at 29.5 deg C, g/cc	0.8682	0.8468
Kinematic Viscosity at 40°C mm ² /s	32	22
Kinematic Viscosity at 100°C mm ² /s	5.42	4.39
Viscosity Index	103	107
Flash Point, COC, °C	220	210
Pour Point, °C	-12	-12
Fire Point COC, °C	260	*
Auto Ignition Temperature °C	353	*
Bulk Oil Temp. (in absence of air) °C	290	*
Film Temp. (in absence of air) °C	310	*
Initial Boiling Point °C	371	*
Final Boiling Point °C	516	*
Product Code	349104	349103

Typical Design Data – Lamina Special 32

Temperature (°C)	0	20	40	100	150	200	250	300
Density (kg/m³)	883	870	857	818	785	753	720	688
Specific heat Capacity, Cp	1,790	1,860	1,930	2,140	2,315	2,490	2,665	2,840
Thermal conductivity (W/m. C)	0,135	0,134	0,132	0,128	0,125	0,121	0,118	0,114

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the EPPCO Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.

Issued by ENOC Marketing LLC, Dubai, U.A.E.

Last Updated in January 2021 MS

PDS V2060121